

## ErisTerminal® SIP Deskset

### VSP715

The compact VSP715 SIP deskset comes with all the essential features you need to keep pace with your business and your budget. Installation is easy and cost-effective with Power over Ethernet (PoE) support, dual Ethernet ports and auto-provisioning. Two programmable buttons provide one-touch access to shared call appearances, ACD, paging and more. Manage multiple calls with advanced call handling features and support for up to two SIP lines/accounts. Support for the G.722 wideband codec for HD Audio means you'll enjoy superior voice quality too.



### VSP715 Key Features

**Advanced call handling.**

Impress customers with comprehensive call handling features that are compatible with hosted and open-source PBX platforms.\*

**Flexibility.**

With support for up to two SIP lines/accounts, you can manage multiple calls with advanced call handling features.

**Intuitive Design.**

You're in business with a user-friendly interface, large backlit display, three soft keys and navigational pad.

**Full-duplex speakerphone.**

Finally, a speakerphone that can keep up with your calls. Increase participation by allowing parties on both ends to speak and be heard – at the same time – for conversations that are more true to life.

**HD voice quality.**

With G.722 wideband codec support for HD audio, calls have never sounded so rich and life-like.

**Dual Ethernet ports.**

Do more with dual Ethernet ports. Connect your desktop computer or laptop to the phone – no need for extra cabling.

**Power over Ethernet (PoE).**

With PoE support, you can locate the phones anywhere that's convenient - no AC outlets or complicated wiring required.

**Three-year warranty.**

Enjoy peace of mind that comes with an industry-leading, standard three-year warranty. VTech also provides advance replacement on warranty claims using new, not refurbished, products.

\*Compatible with Broadsoft®, Genband™, Metaswitch Networks and Asterisk-based platforms.



## Specifications, Weights and Dimensions

- Color: GM (Gun Metal)
- SKU: 03087
- Product dimensions (WxDxH):  
Cordless HS: 1.93" x 1.22" x 6.85"  
Charger: 2.99" x 2.80" x 2.76"  
Cordless HS on Charger: 2.99" x 2.80" x 7.32"
- Product weight: 0.82 lbs.
- Giftbox dimensions (WxDxH):  
4.96" x 2.68" x 7.09"
- Giftbox weight: 0.98 lbs.
- Master pack dimensions (WxDxH):  
10.55" x 5.91" x 7.87"
- Master pack weight: 4.38 lbs.
- Quantity: 4

## AC Adapter Specifications, Weights and Dimensions

- Color: Black
- SKU: 03492
- Product weight: .12 lbs.
- Giftbox dimensions (WxDxH):  
2.36" x 1.69" x 3.14"
- Giftbox weight: 0.15 lbs.
- Inner carton dimensions (WxDxH):  
9.57" x 6.89" x 5.51"
- Inner carton weight: 3.75 lbs.
- Inner carton quantity: 20
- Master pack dimensions (WxDxH):  
21.65" x 10.16" x 11.81"
- Master pack weight: 22.53 lbs.
- Quantity: 120

## Interface

- Dual Ethernet ports – 10/100 Mbps
- Base power: AC adapter (optional) and Class 2 Power over Ethernet (PoE)

## Display, Keys and Indicators

- 158 x 57 pixels (w x h) LCD resolution
- LCD backlighting (white)
- 3 soft keys
- 7 dedicated feature keys
- 2 programmable feature keys
- 4-way navigational pad
- Message waiting LED indicators

## Audio

- Full-duplex base speakerphone
- HAC Receiver
- 2.5 mm corded headset jack
- HD Voice for receiver

## Phone Features

- Supports up to 2 SIP account registrations
- Local phonebook up to 200 entries
- Phonebook import/export
- LDAP/Broadsoft remote phonebook
- Call history up to 200 entries
- Shared Call Appearance (SCA)/ Bridged-Line Appearance (BLA)
- Do Not Distrurb (DND)
- Busy lamp fields (BLF)
- 3-way local conference
- N-way network conference
- Call barring/blocking (block anonymous/blacklist)
- Dial plan/digit map
- Hotline
- Intercom
- Mute
- Redial
- 10 speed dial entries
- Call transfer: blind/attended
- Call hold
- Call park
- Call pick up
- Call forwarding: per-line basis (busy/always/no answer)
- Caller ID
- Phonebook matching (incoming and outgoing calls)
- Multicast paging
- Multi-language support
- Automatic Call Distribution (ACD)

## Customization

- Soft key configuration
- Custom startup and idle logo
- Web interface configuration (admin & user)
- Custom default file

## Security

- 802.1x
- 802.1pq
- Transport Layer Security (TLS)
- AES encryption of config file for provisioning (128 / 64 / 32 / 16 bits)
- LLDP-MED

## Network

- STUN
- NAT
- RTP, SRTP
- SNTP
- VLAN
- Failover support and server redundancy
- Layer 3 QoS (ToS, Diffserv)

## Voice Codec

- G.711 a-law & u-law
- G.722
- G.726
- G.729

## Provisioning

- HTTP, HTTPS, FTP, TFTP
- DHCP options: 66, 159,160
- PnP

## Maintenance

- Diagnostic: pcap trace
- Schedule Resync – time and day setting
- Syslog

## Compatibility

- Broadsoft® Broadworks
- Asterisk-based platforms
- Metaswitch Networks
- Genband™

## Other

- 3-year standard warranty
- Optional AC adapter: VSP715-ADPT
- Advanced product replacement for warranty claims with new product